US009638386B2

(12) **United States Patent**
Iwasaki

(10) **Patent No.: US 9,638,386 B2**
(45) **Date of Patent: May 2, 2017**

(54) **LIGHTING FIXTURE FOR VEHICLE**

(71) Applicant: **ICHIKOH INDUSTRIES, LTD.**, Isehara-shi, Kanagawa-ken (JP)

(72) Inventor: **Kazunori Iwasaki**, Isehara (JP)

(73) Assignee: **ICHIKOH INDUSTRIES, LTD.**, Isehara-Shi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 6 days.

(21) Appl. No.: **14/436,178**

(22) PCT Filed: **Oct. 10, 2013**

(86) PCT No.: **PCT/JP2013/077576**
§ 371 (c)(1),
(2) Date: **Apr. 16, 2015**

(87) PCT Pub. No.: **WO2014/061542**
PCT Pub. Date: **Apr. 24, 2014**

(65) **Prior Publication Data**

US 2015/0260367 A1 Sep. 17, 2015

(30) **Foreign Application Priority Data**

Oct. 18, 2012 (JP) 2012-230905

(51) **Int. Cl.**
F21V 5/04 (2006.01)
F21S 8/10 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***F21S 48/2212*** (2013.01); ***B60Q 1/24*** (2013.01); ***F21S 48/1154*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC .. F21S 48/1266; F21S 48/1275; F21S 48/215; F21S 48/2212; F21S 48/1154;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,972,307 A 11/1990 Takatsuji et al.
8,007,150 B2 * 8/2011 Yagi F21S 48/1154 362/520
(Continued)

FOREIGN PATENT DOCUMENTS

DE 34 17 034 A1 11/1985
DE 10 2005 030 932 A1 1/2007
(Continued)

Primary Examiner — Peggy Neils
(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **ABSTRACT**

It is difficult to efficiently control and design light distribution in the conventional lighting fixture for a vehicle. The present invention is provided with a semiconductor-type light source (**2**) and a lens (**3**). The lens (**3**) is configured from a first lens part (**31**), a second lens part (**32**), and a third lens part (**33**). A light-collecting pattern (SP) is formed in the first lens part (**31**). A first diffusing pattern (DWP) is formed in the second lens part (**32**). A second diffusing pattern (UWP) is formed in the third lens part (**33**). As a result, light distribution can be efficiently controlled and designed in the present invention.

7 Claims, 8 Drawing Sheets